

**IPP Solutions, LLC**

5192 Bolsa Ave, Suite 5  
Huntington Beach, CA 92649 US  
+18582329265  
analiza@ippsolutions.com  
www.ippsolutions.com

**INVOICE**

<b>BILL TO</b>	<b>SHIP TO</b>	<b>SHIP DATE</b>	08/11/2025	<b>INVOICE</b>	2025-323
Raef Satti	Raef Satti	<b>SHIP VIA</b>	LTL	<b>DATE</b>	08/06/2025
Formula Arabia Contracting Company	Formula Arabia Contracting Company			<b>TERMS</b>	Due on receipt
Saudi Arabia Almadinah Province,	Saudi Arabia Almadinah Province,			<b>DUE DATE</b>	08/06/2025
Yanbu, 46429, King Abdul Aziz road,	Yanbu, 46429, King Abdul Aziz road,				
2920, 2nd floor, Alshulaa Ave.	2920, 2nd floor, Alshulaa Ave.				

\*\*\***HS CODE: 8413810040 - PUMPS FOR LIQUIDS, NESOI\*\*\***

SKU	ACTIVITY	DESCRIPTION	QTY	RATE	AMOUNT
20001- PipeCaster Pro Gen 4 EXT	PipeCaster Pro Gen 4 EXT	<p>PipeCaster Pro Gen 4 EXT S/N: PCP-V1-714-000-340</p> <p>For Pipe size 2" to 24", Manhole rehabilitation, Holding tanks and many other applications.</p> <ul style="list-style-type: none"> <li>- Two Component System</li> <li>- 1:1, 2:1 and 3:1 Ratios Available</li> <li>- Pumps many Epoxies, Polyurethanes &amp; Polyurea's</li> <li>- Very affordable And Reliable</li> <li>- Easy to use</li> <li>- Adjustable Volume Dispenser</li> <li>- Moving Parts fully enclosed for safety</li> <li>- Removable Stainless-steel tanks</li> <li>- Gear driven pumps for easy ratio changes</li> <li>- Compact unit</li> <li>- Unit mounted on 'EZ-Ride' Casters</li> <li>- Complete set with hoses and applicator</li> <li>- Easy to clean</li> <li>- Heater bands option</li> <li>- Battery / Inverter use option</li> </ul> <p>Specifications:</p> <ul style="list-style-type: none"> <li>-Weight: Basic Pump 170 lbs. dry. Extra equipment not included.</li> <li>-Height:31.5" (3 gal tanks), 42"</li> <li>-Width: 20"</li> <li>-Length: 33"</li> <li>-Motor: CNC motor with Gearbox</li> <li>-Pumps: Internal rotary gear pumps</li> <li>-Tanks: 3 gallons</li> <li>-Oil free electrical air compressor with soundproof cabinet</li> <li>-Internal compressor with 2HP motor and 10gl Steel Tank</li> <li>-External compressor 27 Gallon, 200 PSI</li> <li>High-Performance with 50-foot air hose</li> <li>-Power: 110 V 5 A, 220 V version available</li> <li>-Wheels: 4", swivel wheels with brakes</li> </ul>	1	53,439.75	53,439.75

All sales and estimates are governed by our "Sales Terms" which you will find on our website at  
[www.ippsolutions.com/salesterms](http://www.ippsolutions.com/salesterms).

- Control: 2 dual port manifold, digital speed control. Low voltage control line to applicator, programmable
- Viscosity: approx. 50 – 2000 cps, depending on material.
- Flow Rate: approx. 0.1 to >1 gallon per minute
- Ratios: 1:1 by volume ratio standard, other ratios available
- 1 Pneumatic Spray Motor (mini)
- 1 Pneumatic Spray Motor (maxi)
- 1 Pneumatic Spray Gun with 2-1/2gallon pressure primer resin tank including 100ft of hoses 8mm.
- 2 sets Air-hoses in 6mm 100 feet
- 2 sets of Air hoses 10mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 8mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 10mm 400 feet
- 1 Remote Control
  
- 1 Pulling Device  
PD-V1-714-000-145
  
- 1 Toolbox with Tools, spare parts and push to connect fittings.

3388PT	3388PT - Pan and tilt Pipe inspection camera, with 60mrod cable dia. 8mm, with 28mm pan and tilt ca	3388PT - Pan and tilt Pipe inspection camera, with 60mrod cable dia. 8mm, with 28mm pan and tilt camera head.  S/N: PCP-V1-714-000-326	1	7,875.00	7,875.00
R-MILL-36-US	R-MILL-36-US - Cleaning machine US (With 36 meters of 12mm cable)	Renssi Drain Cleaning Machine R-MILL-36 S/N: R-MILL-36-US-101-021  Renssi Drain Cleaning Machine with 36m of 12mm Cable With 36 meters of 12mm cable Weight 118kg + control unit 12kg Outer dimensions Width 560mm, Length 870mm, Height 1190mm Cable Size 12mm Max RPM 2800/min (1500/min when using 110V operating voltages) Output 1500W Operating Voltages 230V Material Aluminum Safety foot pedal, easy to move, lockable front wheels, narrow model, light machine  120 feet of 1/2-inch shaft, with a narrow structure that is easy to move around. It is lightweight at approximately 200 pounds, and includes a detachable power cord and pedal cord, integrated control unit with an easy access while operating, handles in front and back for easy lifting, and rubber feet on the side if it is laid down during transport. It is	1	12,200.00	12,200.00

recommended for use on pipe sizes from 3 to 8 inches.

REN-GRI-KIT-1	Renssi grinding kit toolbox	Renssi grinding kit toolbox	1	1,371.15	1,371.15
REN-CUT-KIT-1	Renssi cutter kit toolbox	Renssi cutter kit toolbox	1	1,995.50	1,995.50

\*\*\*THIS INVOICE WAS CREATED AS COMMERCIAL INVOICE ONLY\*\*\*

SUBTOTAL	76,881.40
DISCOUNT 5%	-3,844.07
TAX	0.00
TOTAL	73,037.33

BALANCE DUE **\$73,037.33**