

IPP Solutions, LLC

5192 Bolsa Ave, Suite 5
 Huntington Beach, CA 92649 US
 (714) 410-0707
 analiza@ippsolutions.com
 www.ippsolutions.com

**COMMERCIAL INVOICE*******HS CODE: 8413810040 - PUMPS FOR LIQUIDS, NESOI*******INVOICE**

BILL TO	SHIP TO	SHIP VIA	FOB	INVOICE	2026-139
Taein Lee	Taein Lee			DATE	03/24/2026
Highcoatic Co., LTD	Highcoatic Co., LTD			TERMS	Due on receipt
108 Munhawa-ro	108 Munhawa-ro			DUE DATE	03/24/2026
Idong-eup	Idong-eup				
Yongin-si, Gyeonggi-do	Yongin-si, Gyeonggi-do				
South Korea	South Korea				

SKU	ACTIVITY	DESCRIPTION	QTY	RATE	AMOUNT
20001-GEN 5	20001-PipeCaster Pro Gen 5	PipeCaster™ Pro Gen 5 – System S/N: PCP-V1-714-000-401	1	68,500.00	68,500.00

The PipeCaster™ Pro Gen 5 is a high-performance Spray In Place Pipe (SIPP) application system engineered for structural rehabilitation of 2"–24" pipelines. Designed for versatility, precision, and large-scale productivity, the Gen 5 supports multiple mix ratios (1:1, 2:1, 3:1) for epoxies, polyurethanes, and polyurea, making it suitable for residential, commercial, industrial, and municipal lining projects. The system integrates dual air compressors, digital flow through heating, and real time RPM control to ensure consistent material performance and uniform application in all jobsite environments.

Technical Specifications:

- Pipe Capacity: 2" to 24"
- Mix Ratios: 1:1 standard (2:1 and 3:1 optional)
- Flow Rate: Approx. 0.1 to >1 gallon per minute
- Material Viscosity Range: Approx. 50–2000 cps
- Pumps: Internal rotary gear pumps (fully enclosed for safety)
- Motor: CNC motor with integrated gearbox
- Heating System:
 - Two (2) 1000W flow through digital heaters (110V)
 - Digital temperature control
- RPM Meter: Digital display for real time spray control
- Power: 110V / 5A (220V version available)
- Tank Capacity: Two stainless steel 7-gallon

All sales and estimates are governed by our "Sales Terms" which you will find on our website at www.ippsolutions.com/salesterms.

resin tanks

- Dimensions: 31.5"-42" H x 20" W x 33" L
- Weight: 170 lbs. (dry, without accessories)
- Mobility: 4" swivel casters with brakes
- Air System:
 - Quiet internal 2HP compressor
 - External 27-gallon compressor (200 PSI) with 50 ft hose

Starter Kit Includes:

- 1 Pneumatic Spray Motor (mini)
- 1 Pneumatic Spray Motor (maxi)
- 1 Pneumatic Spray Gun with 2-1/2gallon pressure primer resin tank including 100ft of hoses 8mm.
- 2 sets Air-hoses in 6mm 100 feet
- 2 sets of Air hoses 10mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 8mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 10mm 400 feet

- 1 Remote Control
- 1 Pulling Device
PD-V1-714-000-175

- 2 Heater Buckets
- Laser Thermometer
- 1 Toolbox with Tools, spare parts and push to connect fittings.

NO AIR COMPRESSOR & GENERATOR

SET EQUIPMENT VOLTAGE 220V (KOREA)

10401	Miscellaneous Parts	Miscellaneous Parts CREDIT FOR THE COMPRESSOR & GENERATOR	1	-2,500.00	-2,500.00
-------	---------------------	---	---	-----------	-----------

We appreciate your business.

Accounts not paid within terms are subject to a 1.5% monthly finance charge.

SUBTOTAL	66,000.00
DISCOUNT 15%	-9,900.00
TAX	0.00
TOTAL	56,100.00
BALANCE DUE	\$56,100.00