




LOS ANGELES AREA
CHAMBER OF COMMERCE

CERTIFICATE OF ORIGIN

ORIGINAL

TO VALIDATE, GO TO
VERIFY.FTGS.US

Certificate Number : **LA-COO-63143-689a6de7877cf**
Date : **August 11, 2025**

Seller (Exporter) IPP SOLUTIONS LLC 5192 Bolsa Avenue Huntington Beach CA USA	Transport Type Air	Port of Loading King Abdulaziz Airport Jeddah
	Destination Country Saudi Arabia	Destination Port King Abdulaziz Airport Jeddah
	Export Date 2025-08-11	Exporting Carrier EXFREIGHT ZETA, 674423
	Import Permit Number *****	Bill of Lading / AWB 60111223052
Consignee Formula Arabia Contracting Company King Abdul Aziz road 2920 Alshulaa Ave 2nd floor Yanbu Al Madinah, Province 46429 SA Saudi Arabia	Owner or Agent PRIORITY 1	Forwarding Agent PRIORITY 1
	Remarks Consignor reference: 2025-323	
Buyer (Importer)		

Description (May include notes on Quantity, Item Number, Marks and Numbers, Kind of Packages.)	Weight	Country of Origin
TOOLS & MACHINERY H.S.Code: 8413810040 -----end of products-----	1140 =====	United States =====

Name of Authorized Trade Association



Ben Samia

Authorized Signature **Ben Samia**

The Applicant (or the Applicant on behalf of the Consignor), by utilizing this document, certifies that:

- The above-mentioned goods originate in the country(ies) specified above and comply with the rules of origin applicable in the country(ies) to those goods.
- The information in this certificate and in any documents provided to the Los Angeles Area Chamber of Commerce ("LAACC") is accurate, true and complete.
- The Applicant undertakes to advise LAACC and any other person(s) to whom the applicant provides this Certificate (or to whom the Certificate is provided to with the knowledge of the Applicant) promptly in writing of any inaccuracy, omission or change in such information, or in the origin of goods.
- The Applicant will maintain, and present upon request, such documentation as is necessary to verify the truth, accuracy and completeness of this certificate and accompanying documents.
- In consideration for the LAACC's issuance of this Certificate, the Applicant agrees to release, discharge and hold harmless LAACC from any liability in connection with the issuance of this certificate and to indemnify LAACC in respect of any costs and/or claims made against LAACC in connection herewith.
- The Applicant is authorized to give the undertakings set out herein.

IPP Solutions, LLC

5192 Bolsa Ave, Suite 5
Huntington Beach, CA 92649 US
+18582329265
analiza@ippsolutions.com
www.ippsolutions.com



INVOICE

BILL TO	SHIP TO	SHIP DATE	08/11/2025	INVOICE	2025-323
Raef Satti	Raef Satti	SHIP VIA	LTL	DATE	08/06/2025
Formula Arabia Contracting Company	Formula Arabia Contracting Company			TERMS	Due on receipt
Saudi Arabia Almadinah Province,	Saudi Arabia Almadinah Province,			DUE DATE	08/06/2025
Yanbu, 46429, King Abdul Aziz road,	Yanbu, 46429, King Abdul Aziz road,				
2920, 2nd floor, Alshulaa Ave.	2920, 2nd floor, Alshulaa Ave.				

*****HS CODE: 8413810040 - PUMPS FOR LIQUIDS, NESOI*****

SKU	ACTIVITY	DESCRIPTION	QTY	RATE	AMOUNT
20001- PipeCaster Pro Gen 4 EXT	PipeCaster Pro Gen 4 EXT	PipeCaster Pro Gen 4 EXT S/N: PCP-V1-714-000-340 For Pipe size 2" to 24", Manhole rehabilitation, Holding tanks and many other applications. - Two Component System - 1:1, 2:1 and 3:1 Ratios Available - Pumps many Epoxies, Polyurethanes & Polyurea's - Very affordable And Reliable - Easy to use - Adjustable Volume Dispenser - Moving Parts fully enclosed for safety - Removable Stainless-steel tanks - Gear driven pumps for easy ratio changes - Compact unit - Unit mounted on 'EZ-Ride' Casters - Complete set with hoses and applicator - Easy to clean - Heater bands option - Battery / Inverter use option Specifications: -Weight: Basic Pump 170 lbs. dry. Extra equipment not included. -Height:31.5" (3 gal tanks), 42" -Width: 20" -Length: 33" -Motor: CNC motor with Gearbox -Pumps: Internal rotary gear pumps -Tanks: 3 gallons -Oil free electrical air compressor with soundproof cabinet -Internal compressor with 2HP motor and 10gl Steel Tank -External compressor 27 Gallon, 200 PSI High-Performance with 50-foot air hose -Power: 110 V 5 A, 220 V version available -Wheels: 4", swivel wheels with brakes	1	53,439.75	53,439.75



[Handwritten Signature]

All sales and estimates are governed by our "Sales Terms" which you will find on our website at
www.ippsolutions.com/salesterms.

- Control: 2 dual port manifold, digital speed control. Low voltage control line to applicator, programmable
- Viscosity: approx. 50 – 2000 cps, depending on material.
- Flow Rate: approx. 0.1 to >1 gallon per minute
- Ratios: 1:1 by volume ratio standard, other ratios available
- 1 Pneumatic Spray Motor (mini)
- 1 Pneumatic Spray Motor (maxi)
- 1 Pneumatic Spray Gun with 2-1/2gallon pressure primer resin tank including 100ft of hoses 8mm.
- 2 sets Air-hoses in 6mm 100 feet
- 2 sets of Air hoses 10mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 8mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 10mm 400 feet
- 1 Remote Control

- 1 Pulling Device
PD-V1-714-000-145

- 1 Toolbox with Tools, spare parts and push to connect fittings.

3388PT	3388PT - Pan and tilt Pipe inspection camera, with 60mrod cable dia. 8mm, with 28mm pan and tilt ca	3388PT - Pan and tilt Pipe inspection camera, with 60mrod cable dia. 8mm, with 28mm pan and tilt camera head. S/N: PCP-V1-714-000-326	1	7,875.00	7,875.00
R-MILL-36-US	R-MILL-36-US - Cleaning machine US (With 36 meters of 12mm cable)	Renssi Drain Cleaning Machine R-MILL-36 S/N: R-MILL-36-US-101-021 Renssi Drain Cleaning Machine with 36m of 12mm Cable With 36 meters of 12mm cable Weight 118kg + control unit 12kg Outer dimensions Width 560mm, Length 870mm, Height 1190mm Cable Size 12mm Max RPM 2800/min (1500/min when using 110V operating voltages) Output 1500W Operating Voltages 230V Material Aluminum Safety foot pedal, easy to move, lockable front wheels, narrow model, light machine 120 feet of 1/2-inch shaft, with a narrow structure that is easy to move around. It is lightweight at approximately 200 pounds, and includes a detachable power cord and pedal cord, integrated control unit with an easy access while operating, handles in front and back for easy lifting, and rubber feet on the side if it is laid down during transport. It is	1	12,200.00	12,200.00



[Handwritten signature]

All sales and estimates are governed by our "Sales Terms" which you will find on our website at www.ippsolutions.com/salesterms.

recommended for use on pipe sizes from 3 to 8 inches.

REN-GRI-KIT-1	Renssi grinding kit toolbox	Renssi grinding kit toolbox	1	1,371.15	1,371.15
REN-CUT-KIT-1	Renssi cutter kit toolbox	Renssi cutter kit toolbox	1	1,995.50	1,995.50

THIS INVOICE WAS CREATED AS COMMERCIAL INVOICE ONLY

SUBTOTAL	76,881.40
DISCOUNT 5%	-3,844.07
TAX	0.00
TOTAL	73,037.33
BALANCE DUE	\$73,037.33



[Handwritten signature]

All sales and estimates are governed by our "Sales Terms" which you will find on our website at www.ippsolutions.com/salesterms.

BOL NO: 60111223052

BILL OF LADING

Carrier: EXFREIGHT ZETA, 674423

Shipper

Pickup Date: 07/28/2025

IPP Solutions LLC

5192 Bolsa Avenue, STE 5

Huntington Beach, CA 92649

Analiza Bolt

P: +1 (714) 512-1302

Origin Terminal

Huntington Beach, CA 92649

Phone: P: +1 (714) 512-1302

Destination Terminal

Yanbu, Al Madinah Province 46429 SA

Phone: P:

Consignee

Truckload Identifiers

FORMULA ARABIA CONTRACTING Co.

King Abdul Aziz road 2920

Alshulaa Ave 2nd floor

Yanbu, Al Madinah Province 46429 SA

RAEFF SATTI

Customer Reference: 2025-323

Pickup Hours: 10:00 - 15:00

Delivery Hours: 08:00 - 09:00

3rd Party Bill To

Priority 1 Inc.

P.O. Box 398

North Little Rock, AR 72115

P: +1 (888) 569-8035

Special instructions:Delivery - ETA Del Date: August 7

Freight Terms: ☐Prepaid ☐Collect ☒3rd Party

Units	Type	Pieces	Weight	Dimensions	HM	Item Description
2	Crate	0	1,140 lbs	48" x 48" x 48"		Tools & Machinery
2	0		1,140 lbs			Grand Totals

Where the rate is dependent on value, shippers are required to state specifically in writing the agreed or declared value of the property as follows: "The agreed or declared value of the property is specifically stated by the shipper to be not exceeding ____ per ____."

Remit COD to:

Collect _____ Prepaid _____ Customer check acceptable _____ COD Amount: \$

Note: Liability limitation for loss or damage in this shipment may be applicable. See 49 USC 14706(c)(1)(A) and (B)

Received, subject to individually determined rates or contracts that have been agreed upon in writing between the carrier and shipper, if applicable, otherwise to the rates, classifications and rules that have been established by the carrier and are available to the shipper, on request, and to all applicable state and federal regulations.

Trailer Loaded:

____ by Shipper

____ by Driver

Freight Counted:

____ by Shipper

____ by Driver

The Carrier shall not make delivery of this shipment without payment of and all other lawful charges.

Shipper:_____

Shipper Signature / Date

Consignee Signature / Date

This is to certify that the above-named materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation.

Shipper:_____

Time In:_____ Time Out:_____

This is to certify that the above-named materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation.

Consignee:_____

Time In:_____ Time Out:_____

Carrier Signature / Date

Carrier acknowledges receipt of packages and required placards. Carrier certifies emergency response information was made available and/or carrier has the Department of Transportation emergency response guidebook or equivalent documentation in vehicle. Property described above is received in good order, except as noted.

Carrier:_____

[Handwritten Signature]

LA - C00-63143-689a6de7877cf/August 11, 2025



Truckload Customer SOP

In order prevent mis-delivery release of freight to imposters purporting to act for a selected carrier, it is the responsibility of the Customer / Shipper to ensure that the identity of the pickup driver and the markings on his/her equipment are checked at the point of pickup and to confirm that such markings are consistent with the carrier identified on the Bill of Lading (BOL) issued by Priority1 or generated through Priority1's system.

To help avoid potential fraud, at pickup Customer / Shipper must:

- Verify that the carrier name and MC number on the truck and trailer matches what is shown on the BOL provided by Priority1.
 - If the information does not match or there are any other discrepancies **STOP** and notify your Priority1 representative before loading or releasing the shipment.
- Ask to see the driver's license of the driver, make a copy (or take a digital photo), and retain a copy in your file associated with the shipment.
- Check and record the license plate numbers of each truck and trailer for each shipment and retain copies.

Thank you,

Your Priority1 Team



IPP Solutions, LLC

5192 Bolsa Ave, Suite 5
Huntington Beach, CA 92649 US
+18582329265
analiza@ippsolutions.com
www.ippsolutions.com



Packing Slip

BILL TO	SHIP TO	SHIP DATE	08/11/2025	INVOICE	2025-323
Raef Satti	Raef Satti	SHIP VIA	LTL	DATE	08/06/2025
Formula Arabia Contracting Company	Formula Arabia Contracting Company				
Saudi Arabia Almadinah Province,	Saudi Arabia Almadinah Province,				
Yanbu, 46429, King Abdul Aziz road,	Yanbu, 46429, King Abdul Aziz road,				
2920, 2nd floor, Alshulaa Ave.	2920, 2nd floor, Alshulaa Ave.				

ACTIVITY	DESCRIPTION	QTY
PipeCaster Pro Gen 4 EXT	PipeCaster Pro Gen 4 EXT S/N: PCP-V1-714-000-340 For Pipe size 2" to 24", Manhole rehabilitation, Holding tanks and many other applications. - Two Component System - 1:1, 2:1 and 3:1 Ratios Available - Pumps many Epoxies, Polyurethanes & Polyurea's - Very affordable And Reliable - Easy to use - Adjustable Volume Dispenser - Moving Parts fully enclosed for safety - Removable Stainless-steel tanks - Gear driven pumps for easy ratio changes - Compact unit - Unit mounted on 'EZ-Ride' Casters - Complete set with hoses and applicator - Easy to clean - Heater bands option - Battery / Inverter use option Specifications: -Weight: Basic Pump 170 lbs. dry. Extra equipment not included. -Height:31.5" (3 gal tanks), 42" -Width: 20" -Length: 33" -Motor: CNC motor with Gearbox -Pumps: Internal rotary gear pumps -Tanks: 3 gallons -Oil free electrical air compressor with soundproof cabinet -Internal compressor with 2HP motor and 10gl Steel Tank -External compressor 27 Gallon, 200 PSI High-Performance with 50-foot air hose -Power: 110 V 5 A, 220 V version available -Wheels: 4", swivel wheels with brakes -Control: 2 dual port manifold, digital speed control. Low voltage control line to applicator, programmable -Viscosity: approx. 50 – 2000 cps, depending on material. -Flow Rate: approx. 0.1 to >1 gallon per minute	1



[Handwritten signature]

All sales and estimates are governed by our "Sales Terms" which you will find on our website at www.ippsolutions.com/salesterms.

LA-C00-63143-689a6de7877cf/August 11, 2025

- Ratios: 1:1 by volume ratio standard, other ratios available
- 1 Pneumatic Spray Motor (mini)
- 1 Pneumatic Spray Motor (maxi)
- 1 Pneumatic Spray Gun with 2-1/2gallon pressure primer resin tank including 100ft of hoses 8mm.
- 2 sets Air-hoses in 6mm 100 feet
- 2 sets of Air hoses 10mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 8mm 200 feet
- 4 sets of Nylon hoses high pressure hoses with quick connects 10mm 400 feet
- 1 Remote Control

-1 Pulling Device
PD-V1-714-000-145

-1 Toolbox with Tools, spare parts and push to connect fittings.

3388PT - Pan and tilt Pipe inspection camera, with 60mrod cable dia. 8mm, with 28mm pan and tilt ca

3388PT - Pan and tilt Pipe inspection camera, with 60mrod cable dia. 8mm, with 28mm pan and tilt camera head.

1

S/N: PCP-V1-714-000-326

R-MILL-36-US - Cleaning machine US (With 36 meters of 12mm cable)

Renssi Drain Cleaning Machine R-MILL-36
S/N: R-MILL-36-US-101-021

1

Renssi Drain Cleaning Machine with 36m of 12mm Cable
With 36 meters of 12mm cable
Weight 118kg + control unit 12kg
Outer dimensions Width 560mm, Length 870mm, Height 1190mm
Cable Size 12mm
Max RPM 2800/min (1500/min when using 110V operating voltages)
Output 1500W
Operating Voltages 230V
Material Aluminum
Safety foot pedal, easy to move, lockable front wheels, narrow model, light machine

120 feet of 1/2-inch shaft, with a narrow structure that is easy to move around. It is lightweight at approximately 200 pounds, and includes a detachable power cord and pedal cord, integrated control unit with an easy access while operating, handles in front and back for easy lifting, and rubber feet on the side if it is laid down during transport. It is recommended for use on pipe sizes from 3 to 8 inches.

Renssi grinding kit toolbox

Renssi grinding kit toolbox

1

Renssi cutter kit toolbox

Renssi cutter kit toolbox

1



[Handwritten signature]

All sales and estimates are governed by our "Sales Terms" which you will find on our website at www.ipsolutions.com/salesterms.